

PREBARSO

Glycol beer cooler U14

High performance agitator which is easily serviced or replaced without disconnecting beer lines.

Thermostat and all components accessible from outside the water bath. No need to ever remove chiller lid or disconnect beer lines for field service.

Many connection options available

Beer and coolant lines are grouped for easy installation and maximum cooling effects.

High performance refrigeration package is tuned for tropical climates so your beer is always cold.

Tough, corrosion proof insulated unibody construction. Fewer parts. Longer service.



Specifications

Model	Mini Glycol
Dimensions	450 x 450 x 900 mm
Empty Weight	40 kg
Operational Weight	68 kg
Refrigerant	R134a
Temperature control	Digital
Beer coil (1-4 coils)	AISI-304 8 mm
Compressor	3/8 hp
Cooling capacity @ -10 SST	720 watts
Pull down time @ 30C ambient and water bath	2 hrs
Agitator / pump motor (NGR)	55 watts
Condensor fan motor	25 watts
Voltage	220-230V / 50 HZ / 1 PH
Run current	3.5 amps
Castors included	2" rubber

บริษัท เพรสมัน (ประเทศไทย) จำกัด
 47/9 หมู่ที่ 9 ซอยนาเวศสิทธิ์ ถนนแจ้งวัฒนะ
 ตำบลบางพูด อำเภอปากเกร็ด จังหวัดนนทบุรี 11120

Presmann (Thailand) Co., Ltd.
 47/9 Moo 9, Soi Naweasathien, Chaengwattana Road,
 T. Bangpood, Pakkred, Nonthaburi 11120, Thailand

Tel: +66 (0)29621151 www.PresmannBarSolutions.com



@Presmann



Presmannbarsolutions